





Backs and Support



OWNER'S MANUAL



Thin Articulating Laterals

Owner's Manual for all Stealth
Thin Articulating Lateral
Hardware

Stealth Products strives for 100% customer satisfaction. Your complete satisfaction is important. Please contact us with feedback or to suggest changes that will help improve the quality and usability of our products. You may reach us at:



Stealth Products, LLC
104 John Kelly Drive
Burnet, TX 78611

Phone: (512) 715-9995
Fax: (512) 715-9954

Toll Free: 1(800) 965-9229
Toll Free: 1(800) 806-1225

info@stealthproducts.com
www.stealthproducts.com



MDSS GmbH
Schiffgraben 41
30175 Hannover, Germany



General

Read and understand all instructions before using this product. Failure to adhere to instructions and warnings in this document may result in property damage, injury, or death. Product misuse due to failure of the following instructions will void its warranty.

Immediately discontinue use if any function is compromised, if parts are missing or loose, or if any components show signs of excessive wear. Consult with your supplier for repair, adjustment, or replacement.

Important Information!

All persons responsible for fitting, adjustment, and daily use of the devices discussed in these instructions must be familiar with and understand all safety aspects of the devices mentioned. In order for our products to be used successfully, you must:

- read and understand all instructions and warnings;
- maintain our products according to our instructions on care and maintenance; and
- ensure devices are installed and adjusted by a trained technician.

Supplier Reference

Supplier: _____

Telephone: _____

Address: _____

Purchase Date: _____

Model: _____

The installation instructions will guide you through this product's options and possibilities.

Instructions are written with the expressed intent of use with standard configurations. They also contain important safety and maintenance information, as well as describe possible problems that can arise during use. For further assistance, or more advanced applications, please contact your supplier or Stealth Products at (512) 715-9995 or toll free at (800) 965-9229.

Always keep the operating instructions in a safe place so they may be referenced as necessary.

All information, pictures, illustrations, and specifications are based on the product information that was available at the time of printing. Pictures and illustrations shown in these instructions are representative examples and are not intended to be exact depictions of the various parts of the product.

CAUTION

These products are designed to be fitted, applied, and installed exclusively by a healthcare professional trained for these purposes. The fitting, application and installation by a non-qualified individual could result in serious injury.

Ordering Documentation

You can download additional copies of this manual by accessing the Stealth website (www.stealthproducts.com) and searching "**Thin Articulating Lateral**" in the search bar at the top of the page.

Our products are designed, manufactured, and produced to the highest of standards. If any defect in material or workmanship is found, Stealth Products will repair or replace the product at our discretion. Any implied warranty, including the implied warranties of merchantability and fitness for a particular purpose, shall not extend beyond the duration of this warranty. Stealth Products, LLC does not warrant damage due to, but not limited to:

- misuse, abuse, or misapplication of products, and/or
- modification of product without written approval from Stealth Products, LLC.

Any alteration or lack of serial number, where applicable, will automatically void this warranty.

Stealth Products, LLC is liable for replacement parts only. Stealth Products, LLC is not liable for any incurred labor costs.

No person is authorized to alter, extend, or waive the warranties of Stealth Products, LLC.

Stealth Products warrants against failure due to defective materials or workmanship:

Covers: 180 days

Hardware: 5 years

Electronics: 3 years

In Case of Product Failure

In the event of product failure covered by our warranty, please follow the procedures outlined below:

1. Call Stealth Products at (512) 715-9995 or toll free at (800) 965-9229.
2. Request a Return Authorization form (RA) from the Returns Department and follow documentation instructions.

1.0 Customer Satisfaction i

2.0 Important Information..... ii

3.0 Introduction iii

4.0 Warranty iv

5.0 Table of Contents..... v

6.0 Warning Labels..... vii

 6.1 Warning Labelsvii

 6.2 Limited Liability.....vii

 6.3 Testingvii

7.0 Design and Function..... 1

 7.1 Intended Use 1

 7.2 Features 1

 7.3 Mounting 1

8.0 Features..... 2

 8.1 Thin Articulating Lateral Configurations.....2

9.0 Parts and Accessories 3

 9.1 Lateral Configuration Breakdowns.....3

 9.2 Lateral Component Specifications4

10.0 Installation Instructions 5

 10.1 Preparations6

 10.2 Tools.....6

 10.3 Installation Plan.....6

 10.4 Required Tools.....7

 10.5 Standard Cane Mounting.....7

 10.6 Standard Track Mounting.....8

 10.7 Standard Planar Mounting.....8

11.0 First-Time Use 9

 11.1 Dealer Assistance 9

 11.2 User Testing 9

 11.3 Conditions of Use..... 9

12.0 Maintenance..... 10

 12.1 Cleaning 10




 12.2 Disinfecting..... 10

 12.3 Maintenance..... 11

Warning Labels

6.1

Warnings are included for the safety of the user, client, operator and property. Please read and understand what the signal words **DANGER**, **WARNING**, **CAUTION**, **NOTICE** and **SAFETY** mean, and how they could affect the user, those around the user, and property.

 DANGER	Identifies an imminent situation which, if not avoided, may result in severe injury, death, and/or property damage .
 WARNING	Identifies a potential situation which, if not avoided, may result in severe injury, death, and/or property damage .
 CAUTION	Identifies a potential situation which, if not avoided, may result in minor to moderate injury and/or property damage .
NOTICE	Identifies important information not related to injury, but possible property damage .
SAFETY	Indicates steps or instructions for safe practices, reminders of safe procedures, or important safety equipment that may be necessary.

Limited Liability

6.2

Stealth Products, LLC accepts no liability for personal injury or damage to property that may arise from the failure of the user or other persons to follow the recommendations, warnings, and instructions in this manual. Stealth Products, LLC does not hold responsibility for final integration of final assembly of product to end user. Stealth Products, LLC is not liable for user death or injury.

Testing

6.3

Initial setup and driving should be done in an open area free of obstacles until the user is fully capable of operating the product safely.

Intended Use

7.1

The **Thin Articulating Lateral** is intended for use as a low-profile, adjustable thoracic support attachment for both manual and power wheelchairs. The lateral's thin, lightweight design allows it to be used in limited-space scenarios unsuited for standard lateral support solutions.

A spring-loaded quick-release push latch allows the **Thin Articulating Lateral** to be swung 125° away from the user for easy care and transfer, while each joint of the lateral arm offers 200° of adjustability. Offered in both one- and two-point adjustment models, the lateral accommodates track, cane, planar, Tru Comfort, and All Seasons mounting options.

Fully customizable pads attach easily to the lateral, while slip covers conceal hardware and provide soft, smooth points of contact for users.

Features

7.2

The **Thin Articulating Lateral** features:

- a discreet, unobstructive design;
- one- and two-point adjustment configurations;
- 200° of adjustment at each point;
- multiple mounting styles and options;
- a quick-release lateral swing away latch; and
- soft, unabrasive hardware covers

Mounting


7.3

The **Thin Articulating Lateral** can be mounted to both manual and power wheelchairs, and is compatible with cane, track, planar, Tru Comfort, and All Seasons mounting hardware.

Thin Articulating Lateral Configurations


8.1

Stealth offers three configurations of **Thin Articulating Lateral**:




TWBTL

- Offers one point of adjustment
-



TWBSTL

- Offers two points of adjustment
-




SSTLTA-TB4

- Features left and right laterals as package
- Each lateral offers two points of adjustment
- Laterals include mounted lateral brackets, lateral mounting nuts, two-hole washers

Lateral Configuration Breakdowns


9.1

TWBTL




	Part:
A	Pad Mount
B	Short Swing-Away Block
C	Latch Block
D	Quick-Release Thumb Latch

TWBSTL



	Part:
A	Pad Mount
B	Multi-Adjustment Link
C	Short Swing-Away Block
D	Latch Block
E	Quick-Release Thumb Latch

SSTLTA-TB4




	Part:
A	Pad Mount (2)
B	Multi-Adjustment Link (2)
C	Short Swing-Away Block (2)
D	Latch Block (2)
E	Quick-Release Thumb Latch
F	Lateral Bracket, 125° (2)
G	Lateral Mounting Nut (2)
H	Two-Hole Washer (2)

Lateral Component Specifications


9.2

TWBTL




	Component:	Tool Required:	Torque Specifications:
A	10-32 x 3/8" Socket Head Screws (2)	5/32 hex key	31.7lb-in.

TWBSTL



	Component:	Tool Required:	Torque Specifications:
A	10-32 x 3/8" Socket Head Screws (2)	5/32 hex key	31.7lb-in.

SSTLTA-TB4



	Component:	Tool Required:	Torque Specifications:
A	10-32 x 3/8" Socket Head Screws (4)	5/32 hex key	31.7lb-in.
B	1/4-20 x 3/8" Button Head Screws (4)	5/32 hex key	6.3 lb-ft.
C	M6 x 1 x 16mm Nylon Patch Button Head Screws (4)	4mm hex key	7.8 N-m

Installation Instructions

Preparations

10.1

Only a qualified service technician may install the TFB back and its accessories.



WARNING

Incorrectly installing a **Thin Articulating Lateral** and/or its accessories may damage the hardware and/or injure the user.

Tools

10.2

Use the proper tools to install and adjust the lateral(s) to the desired position(s) for the user. Ensure all torque specifications are followed.



CAUTION

The use of improper tools may cause damage to the device. Not tightening to the torque specification can cause components to fail or cause discomfort to the user.

Installation Plan

10.3

Set up an installation plan before beginning the installation. This plan should take into account:

- where the lateral(s) will be placed;
- how the laterals will function; and
- the space needed for sufficient clearance of other hardware and accessories.




CAUTION

Any connection must always be secured with all delivered screws. Only use the screws provided in the package.

Required Tools

10.4


The tools needed to complete the installation are as follows:



	Tool:
A	5/32 hex key
B	4mm hex key

Standard Cane Mounting

10.5



Step One: Identify the male cane clamp and the female cane clamp.


Step Two: Attach the lateral's latch block to the female cane clamp by inserting the two (2) 1/4-20 x 3/8" button head screws through the face of the latch block and into the female cane clamp, as pictured above.

Step Three: Attach the male tube clamp to the female clamp by, from the opposite side of the wheelchair cane, inserting the two (2) 1/4-20 x 3/4" socket head screws through the male clamp into the interior of the female clamp.

Standard Track Mounting

10.6

(Note: The SSTLTA-TB4 assembly is not compatible with standard track mounting.)




Step One: Loosely attach the track nut to the lateral latch block by inserting the two (2) socket head screws provided through the face of the latch block and into the track nut, as pictured above.

Step Two: Slide the track nut into the corresponding groove in the track mount. Tighten the screws to secure the assembly position.

Standard Planar Mounting

10.7



Step One: Attach the planar mount to the lateral latch block by inserting the two (2) 1/4-20 x 3/4" socket head screws through the face of the latch block and into the planar mount. (The planar mount and the lateral latch block be joined at a 90° angle.)

Step Two: Attach the assembly to the chair by inserting the two (2) 1/4-20 x 3/8" button head screws through the planar mount tracks and into the chair back mounting hardware.

Dealer Assistance

11.1

During first-time use by the client, it is advised that the dealer or service technician not only assembles the product, but also explains the configuration of user positioning to the customer (i.e., the user and/or the attendant). If needed, the dealer can make final adjustments.

User Testing

11.2

It is important that the customer is fully aware of the installation of a **Thin Articulating Lateral**, how to use it, and how it can be adjusted to fit the client comfortably. As a dealer, proceed as follows:

- Explain and show the customer how you have executed the installation and explain the function.

Have the user test the position of the lateral:

- Is the hardware in the proper position for the client?
- Can the user safely operate all controls with minimal effort?

If needed, make any adjustments to the positioning.

Explain possible problems and how to address them to the customer.

Conditions of Use

11.3

Thin Articulating Laterals are intended for use as installed by the dealer, in accordance to the installation instructions in this manual.

- The foreseen conditions of use are communicated by the dealer or service technician to the user and/or attendant during the first-time use.
- If the usage conditions change significantly, please contact your dealer or a qualified service technician to avoid unintended damage.

Cleaning

12.1

- Use a soft cloth to clean the lateral.
- Ensure all cleaners are approved for finished steel, aluminum, plastic, and upholstered surfaces.
- Hand wash foam pad cover with mild, soapy water or detergent, and let dry.
- Use a soft brush to remove dirt and debris in the zipper teeth.

To wash the covers of the laterals:

- Remove the pad/cover from the laterals.
- Machine wash in cold water on delicate cycle and drip dry.

Fabric care instructions can be found on the covers of the cushions and back:

- Remove the pad/cover from the laterals.
- Machine wash in cold water on delicate cycle and drip dry.



WARNING

Do not bleach.
Do not iron.
Do not hand wash in water temperatures above 160°F (70°C).
Do not wash or machine dry.



CAUTION

Take care when removing the back as to not puncture, tear, or otherwise damage the fabric or foam.



CAUTION

Take care when zipping and unzipping the cover to ensure nothing gets caught in the zipper path.

Disinfecting

12.2

- Wipe gently with a cloth dampened with a household disinfectant.
- Allow foam to air dry thoroughly.



WARNING

Do not immerse foam in water.

Maintenance

12.3

These care and guideline instructions will keep the hardware and covers in good condition for a longer period of time and prevent damage:

- Check and re-tighten all fasteners to the proper torque specifications on a regular basis.
- Check pads and covers for any breakdown.
- Repair or replace parts as needed.
- Gently remove dust and dirt from hardware with a damp cloth.

CAUTION

Always check all mounting hardware, making sure each fastener is properly tightened before using the back support.

SAFETY

Replace or repair parts as needed.

CAUTION

250lbs (113.40 kg) user weight limit.

NOTICE

Improper installation or any alteration of a lateral will void its warranty.



Stealth Products, LLC. • info@stealthproducts.com • www.stealthproducts.com
(800) 965-9229 | (512) 715-9995 | 104 John Kelly Drive, Burnet TX 78611